


DIELECTRIC UNION - FEMALE IRON PIPE x SOLDER

- * Sizes: 1/2" - 2"
- * Galvanized x Brass
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * Copper connections: ANSI B 16.18
- * IAPMO / UPC Listed



Part No.	Size	Inner Pack	Master Pack
PK110-050	1/2" x 1/2"	12	144
PK110-075	3/4" x 3/4"	12	144
PK110-755	3/4" x 1/2"	12	144
PK110-100	1" x 1"	12	72
PK110-175	1" x 3/4"	12	72
PK110-125	1-1/4" x 1-1/4"	6	72
PK110-150	1-1/2" x 1-1/2"	6	36
PK110-200	2" x 2"	6	24

DIELECTRIC UNION - MALE IRON PIPE x SOLDER

- * Sizes: 1/2" - 1"
- * Galvanized x Brass
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * Copper connections: ANSI B 16.18
- * IAPMO / UPC Listed



Part No.	Size	Inner Pack	Master Pack
PK111-050	1/2" x 1/2"	12	96
PK111-075	3/4" x 3/4"	12	96
PK111-755	3/4" x 1/2"	12	96
PK111-100	1" x 1"	12	72

DIELECTRIC UNION - FEMALE IRON PIPE x FEMALE BRASS IRON PIPE

- * Sizes: 1/2" - 1"
- * Galvanized x Brass
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * IAPMO / UPC Listed



Part No.	Size	Inner Pack	Master Pack
PK112-050	1/2" x 1/2"	10	100
PK112-075	3/4" x 3/4"	10	100
PK112-100	1" x 1"	5	50
PK112-125	1-1/4" x 1-1/4"	5	40
PK112-150	1-1/2" x 1-1/2"	5	20
PK112-200	2" x 2"	5	20

DIELECTRIC UNION - FEMALE IRON PIPE x FEMALE IRON PIPE

- * Sizes: 1/2" - 2"
- * Galvanized x Galvanized
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * IAPMO / UPC Listed



Part No.	Size	Inner Pack	Master Pack
PK113-050	1/2" x 1/2"	10	100
PK113-075	3/4" x 3/4"	10	100
PK113-100	1" x 1"	5	50
PK113-125	1-1/4" x 1-1/4"	5	40
PK113-150	1-1/2" x 1-1/2"	5	20
PK113-200	2" x 2"	2	20

DIELECTRIC UNION - FEMALE IRON PIPE x FEMALE IRON PIPE (BLACK)

- * Sizes: 1/2" - 2"
- * Black steel x Black steel
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * For use with black pipe
- * IAPMO / UPC Listed



Part No.	Size	Inner Pack	Master Pack
PK114-050	1/2" x 1/2"	10	100
PK114-075	3/4" x 3/4"	10	100
PK114-100	1" x 1"	5	50
PK114-125	1-1/4" x 1-1/4"	5	40
PK114-150	1-1/2" x 1-1/2"	5	20
PK114-200	2" x 2"	2	20

DIELECTRIC UNION - FEMALE IRON PIPE x SOLDER- FLANGED

- * Sizes: 2-1/2" - 4"
- * Galvanized x Brass
- * Maximum working water pressure: 250PSI (ANSI 16.39)
- * Maximum working water temperature: 210°F
- * Thread connections: ANSI B 1.20.1
- * Copper connections: ANSI B 16.18
- * IAPMO / UPC Listed



2-1/2" - 3"



4"



Part No.	Size	Inner Pack	Master Pack
PK115-250	2-1/2" x 2-1/2"	1	4
PK115-300	3" x 3"	1	4
PK115-400	4" x 4"	1	2

DIELECTRIC FITTING

RUBBER WASHER & INSULATOR FOR DIELECTRIC UNION

- * Sizes: 1/2" - 2"
- * For water
- * 210°F temperature rating



Part No.	Size	Inner Pack	Master Pack
RUBBER WASHER			
PH131-050	1/2"	10	100
PH131-075	3/4"	10	100
PH131-100	1"	10	100
PH131-125	1-1/4"	10	100
PH131-150	1-1/2"	10	100
PH131-200	2"	10	100
INSULATOR			
PH132-050	1/2"	10	100
PH132-075	3/4"	10	100
PH132-100	1"	10	100
PH132-125	1-1/4"	10	100
PH132-150	1-1/2"	10	100
PH132-200	2"	10	100

DIELECTRIC FITTING